



AUT (Wheels and Castors) Ltd are a national castor company that have supplied quality wheels and castors for the last 35 years.

All our castors are tested to all relevant European norms so you can be confident on quality and conformity.

Wheels and Castors

Our Utility Range has been designed specifically to cater for as much as 90% of the everyday applications of wheels and castors.

- The range is versatile meaning it can be used across a broad spectrum of industries and applications.
- It is extremely cost effective.
- It has been designed to look as stylish as possible, meaning it will complement your finished products.
- It offers a broad range of carrying capacities meaning you can be confident we can meet any weight specific requirements,
- The range is also available in stainless steel making it perfect for hygienic or clean areas.

This is of course a standard range of castors, there are many other options available upon request. We have included our series 64 range which shows some of our heavier duty castors for your reference.

AT

GREY TPR TYRED APPARATUS WHEELS & CASTORS



85 shore A



50mm



50Kg



plain bore



ball bearing

- Polypropylene light grey wheel centre with thermoplastic rubber dark grey tread.
- Pressed steel, zinc plated castor body.

- Plain bearing without threadguards. Single ball bearing has plastic threadguards.
- Ideal for use in manual handling, medical centres and the hotel industry.



Apparatus Castors



50	19	70	60x60	48/39x48/39	6.3	11	50	swivel	fixed	+ total brake	bolt hole	bolt hole + total brake
								AT050P2Z21	AT050P3Z21	AT050P4Z21	AT050P5Z21	AT050P6Z21
50	19	70	60x60	48/39x48/39	6.3	11	50	swivel	fixed	+ total brake	bolt hole	bolt hole + total brake
								AT050B2Z21	AT050B3Z21	AT050B4Z21	AT050B5Z21	AT050B6Z21



GREY TPR TYRED APPARATUS WHEELS & CASTORS



- Plain bearing without threadguards.
- Single ball bearing has plastic threadguards.
- Ideal for use in manual handling, medical centres and the hotel industry.

ALUMINIUM PEDAL



																									
75	25	100	60x60	48/38x48/38	6.3																				
100	32	135	77x67	61.5/56x51.5/46.56	8.5																				
125	32	160	77x67	1.5/56x51.5/46.5	8.5																				
125	32	160	95x70	55x50	11																				
150	32	185	77x67	61.5/56x51.5/46.5	8.5																				

ALUMINIUM PEDAL



							Kg	swivel	fixed	+ total brake	+ total brake	
75	25	100	60x60	48/38x48/38	6.3		75	AT075B2Z21	AT075B3Z21	AT075B4Z21	-	
100	32	135	77x67	61.5/56x51.5/46.56	8.5		100	AT100B2Z21	AT100B3Z21	AT100B4Z21	AT100B4Z22	
125	32	160	77x67	1.5/56x51.5/46.5	8.5		100	AT125B2Z21	AT125B3Z21	AT125B4Z21	AT125B4Z22	
125	32	160	95x70	75x50	11		100	AT125B2Z31	AT125B3Z31	AT125B4Z31	AT125B4Z32	
150	32	185	77x67	61.5/56x51.5/46.5	8.5		100	AT150B2Z21	AT150B3Z21	AT150B4Z21	AT150B4Z22	

ALUMINIUM PEDAL



							 swivel	 + total brake	 + total brake				
75	25	100		11		75	AT075P5Z21	AT075P6Z21	-				
100	32	135		11		100	AT100P5Z21	AT100P6Z21	AT100P6Z22				
125	32	160		11		100	AT125P5Z31	AT125P6Z31	AT125P6Z32				
150	32	185		11		100	AT150P5Z21	AT150P6Z21	AT150P6Z22				

ALUMINIUM PEDAL



								 swivel		 + total brake		 + total brake			
75	25	100		11		75		AT075B5Z21		AT075B6Z21		-			
100	32	135		11		100		AT100B5Z21		AT100B6Z21		AT100B6Z22			
125	32	160		11		100		AT125B5Z31		AT125B6Z31		AT125B6Z32			
150	32	185		11		100		AT150B5Z21		AT150B6Z21		AT150B6Z22			



AT

GREY TPR TYRED APPARATUS WHEELS & CASTORS



95 shore A



50mm - 75mm



50Kg - 100Kg


plain
bore

ball
bearing

- Polypropylene light grey wheel centre with thermoplastic rubber dark grey tread.
- Pressed steel, zinc plated castor body.

- Plain bearing without threadguards. Single ball bearing has plastic threadguards.
- Ideal for use in manual handling, medical centres and the hotel industry.

Top Plate Castors



50	19	70	60x60	48/38x48/38	6.3		70	swivel	swivel brake	swivel	swivel brake		
75	25	102	77x67	61.5/56x51.5/46.5	8.5		100	AT050P2Z81 AT075P2Z81	AT050P4Z81 AT075P4Z81	AT050B2Z81 AT075B2Z81	AT050B4Z81 AT075B4Z81		



Bolt Hole Castors



50	19	70		11			70	swivel	swivel brake	swivel	swivel brake		
75	25	102		11			100	AT050P5Z81 AT075P5Z81	AT050P6Z81 AT075P6Z81	AT050B5Z81 AT075B5Z81	AT050B6Z81 AT075B6Z81		





GREY NON MARKING RUBBER TYRE ON
BLACK PLASTIC CENTRE WHEELS & CASTORS





- Polypropylene black wheel centre with grey solid rubber tread.
- Pressed steel, zinc plated castor body.
- Without threadguards.
- Ideal for handling trolleys.

BLACK RUBBER TYRE ON
BLACK PLASTIC CENTRE WHEELS & CASTORS



- Black polypropylene wheel centre with black solid rubber tread.
- Pressed steel, zinc plated castor body.
- Without threadguards.
- Ideal for handling trolleys.

GREY RUBBER TYRE ON
STEEL CENTRE WHEELS & CASTORS





- Steel centre wheel with grey solid rubber tread.
- Pressed steel, zinc plated castor body.
- Without threadguards.
- Ideal for handling trolleys.



---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--

INJECTION MOULDED POLYURETHANE TYRE BONDED TO NYLON CENTRE WHEEL & CASTORS



- Red polyurethane tyre on grey polyamide centre wheel.
- Pressed steel, zinc plated castor body.
- Roller bearing has metal threadguards.
Ball bearing has plastic threadguards.
- Ideal for handling trolleys.



									 Kg	roller bearing	ball bearing					
80	30	12	39						120	E080R1021	-					
80	30	8	40						100	-	E080B1021					
100	32	12	40						150	E100R1021	-					
100	32	15	40						150	-	E100B1021					
125	32	15	50						200	E125R1021	E125B1021					
160	40	20	59						300	E160R1055	E160B1055					
200	50	20	59						350	E200R1055	E200B1055					



---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--



							 Kg	 swivel	 fixed	 + total brake			
80	30	108	105x80	80/77x60	9		120	E080BZ2Z1	E080B3Z21	E080B4Z21			
100	32	125	105x80	80/77x60	9		150	E100BZ2Z1	E100B3Z21	E100B4Z21			
125	32	155	105x80	80/77x60	9		200	E125BZ2Z1	E125B3Z21	E125B4Z21			
160	40	195	135x110	105x84/76	11		300	E160BZ2Z5	E160B3Z55	E160B4Z55			
200	50	235	135x110	105x84/76	11		350	E200BZ2Z55	E200B3Z555	E200B4Z555			

Bolt Hole Castors available on request.



2

3

roller bearing



- 

									swivel		+ total brake						
80	34	105			13		130		F080R5Z21		F080R6Z21						
100	36	125			13		150		F100R5Z21		F100R6Z21						
125	38	155			13		150		F125R5Z21		F125R6Z21						
160	40	195			13		200		F160R5Z21		F160R6Z21						
200	50	235			13		200		F200R5Z21		F200R6Z21						



Utility RANGE

WHITE POLYPROPYLENE WHEELS & CASTORS



- Plain bearing without threadguards.
Roller bearing has metal threadguards.
- Ideal for handling trolleys.

Plain bore larger sizes available on request.

														
80	34	105	105x80	87/77x60	9	80	G080R2Z21	G080R3Z21	G080R4Z21					
100	36	125	105x80	87/77x60	9	100	G100R2Z21	G100R3Z21	G100R4Z21					
125	38	155	105x80	87/77x60	9	150	G125R2Z21	G125R3Z21	G125R4Z21					
125	38	155	135x110	105x84/76	11	200	G125R2Z25	G125R3Z25	G125R4Z25					
160	40	195	135x110	105x84/76	11	200	G160R2Z21	G160R3Z21	G160R4Z21					
200	50	235	135x110	105x84/76	11	250	G200R2Z21	G200R3Z21	G200R4Z21					

									 swivel		 + total brake					
80	34	104			13		70		G080R5Z21		G080R6Z21					
100	36	124			13		90		G100R5Z21		G100R6Z21					
125	38	154			13		140		G125R5Z21		G125R6Z21					
160	40	194			13		200		G160R5Z21		G160R6Z21					
200	50	234			13		200		G200R5Z21		G200R6Z21					







3

- Roller bearing without threadguards. Ball bearing has plastic threadguards.
- Ideal for handling trolleys.



									 swivel		 + total brake						
80	35	104			13		130		H080B5Z21		H080B6Z21						
100	35	124			13		150		H100B5Z21		H100B6Z21						
125	38	154			13		150		H125B5Z21		H125B6Z21						
160	46	194			13		200		H160B5Z21		H160B6Z21						
200	46	234			13		250		H200B5Z21		H200B6Z21						

THERMOPLASTIC RUBBER TYRED WHEELS WITH POLYPROPYLENE CENTRE & STANDARD CASTORS



- Light grey polypropylene wheel with dark grey thermoplastic rubber tread.
- Pressed steel, zinc plated castor body.
- Roller bearing has metal threadguards. Ball bearing has plastic threadguards.
- Ideal for handling trolleys.

											roller bearing			ball bearing				
80	30	12	39					70		K080R1021			-					
80	30	8	40					70		-			K080B1021					
100	32	12	40					100		K100R1021			-					
100	32	15	40					100		-			K100B1021					
125	32	15	50					135		K125R1021			K125B1021					
160	40	20	59					200		K160R1021			K160B1021					
200	50	20	59					205		K200R1021			K200B1021					

																																																																																																																																					
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--

							Kg	swivel	fixed	+ total brake				
80	30	108	105x80	80/77x60	9		70	K080B2Z21	K080B3Z21	K080B4Z21				
100	32	125	105x80	80/77x60	9		100	K100B2Z21	K100B3Z21	K100B4Z21				
125	32	155	105x80	80/77x60	9		135	K125B2Z21	K125B3Z21	K125B4Z21				
160	40	195	135x110	105x84/76	11		200	K160B2Z21	K160B3Z21	K160B4Z21				
200	50	235	135x110	105x84/76	11		205	K200B2Z21	K200B3Z21	K200B4Z21				

Bolt Hole Castors available on request.

Page



Page 255

LDV Series

Pressed Steel Castor

- Load capacities from 50kg up to 250kg
- Wheel sizes from 50mm to 200mm
- Strong pressed steel bracket
- Double ball race swivel head

White Polypropylene

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
50	18	Plain	50x50	36x36	32	72	50	LSV050PP	LSV050PPBR	N/A
75	25	Plain	75x60	55x42	34	95	70	LSV075PP	LSV075PPBR	LFV075PP
100	35	Plain	102x84	80x60	34	128	125	LSV100PP	LSV100PPBR	LFV100PP
125	37	Plain	102x84	80x60	34	155	160	LSV125PP	LSV125PPBR	LFV125PP
160	40	Plain	135x110	105x80	48	190	200	LSV160PP	LSV160PPBR	LFV160PP
200	40	RB	135x110	105x80	58	235	250	LSV200PP	LSV200PPBR	LFV200PP



Grey Rubber Tyre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
50	18	Plain	50x50	36x36	32	72	50	LSV050RP	LSV050RPBR	N/A
75	25	Plain	75x60	55x42	34	95	50	LSV075RP	LSV075RPBR	LFV075RP
100	24	RB	102x84	80x60	34	128	70	LSV100RP	LSV100RPBR	LFV100RP
125	24	RB	102x84	80x60	34	155	100	LSV125RP	LSV125RPBR	LFV125RP
160	22	Plain	135x110	105x80	48	190	135	LSV160RP	LSV160RPBR	LFV160RP
200	30	Plain	135x110	105x80	58	235	205	LSV200RP	LSV200RPBR	LFV200RP



Black Rubber Tyre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
75	22	RB	75x 60	55x42	32	95	50	LSV075RMB	LSV075RMBBR	LFV075RMB
100	24	RB	102x84	80x60	34	128	70	LSV100RMB	LSV100RMBBR	LFV100RMB
125	24	RB	102x84	80x60	34	155	100	LSV125RMB	LSV125RMBBR	LFV125RMB
160	22	RB	135x110	105x80	48	190	160	LSV160RMB	LSV160RMBBR	LFV160RMB
200	30	RB	135x110	105x80	58	235	205	LSV200RMB	LSV200RMBBR	LFV200RMB



All available in the following types

Top plate



Swivel

Swivel Brake

Fixed

LDV Series

Pressed Steel Castor

- Load capacities from 50kg up to 250kg
- Wheel sizes from 50mm to 200mm
- Strong pressed steel bracket
- Double ball race swivel head

White Polypropylene

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked
50	20	Plain	10	23	72	50	LSV050PPBH	LSV050PPBHBR
75	20	Plain	10	30	100	70	LSV075PPBH	LSV075PPBHBR
100	20	Plain	12	38	135	80	LSV100PPBH	LSV100PPBHBR
125	35	Plain	12	38	155	125	LSV125PPBH	LSV125PPBHBR



Grey Rubber Tyre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked
50	18	Plain	10	23	72	50	LSV050RPBH	LSV050RPBHBR
75	21	Plain	10	30	100	70	LSV075RPBH	LSV075RPBHBR
100	27	Plain	12	38	135	80	LSV100RPBH	LSV100RPBHBR
125	27	Plain	12	38	155	100	LSV125RPBH	LSV125RPBHBR



All available in the following types
Bolt hole



Swivel



Swivel Brake

Expander Fittings

This range of Nylon fittings allow castors to be fitted to hollow tube constructed equipment and furniture. Available loose or factory fitted to your choice of castor.

Tube Size (Internal mm)		Catalogue Reference	
Min	Max	Round	Square
19	21.5	WR07 19/21.5	n/a
21.5	24	WR07 21.5/24	WR47 21.5/24
24	27	WR07 24/27	WR47 24/27
27	30	WR07 27/30	WR47 27/30
31	35	WR07 31/35	n/a
32	35	n/a	WR47 32/35
36	40	n/a	WR47 36/40

All available in the following types
Expander Fittings



Round



Square



MDV Series

Pressed Steel Castor

- Load capacities from 70kg up to 350kg
- Wheel sizes from 80mm to 200mm
- Strong pressed steel bracket
- Double ball race swivel head
- Bottle cap thread guards

Red Polyurethane Tyre/Nylon Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
80	30	RB	105x80	80x60	40	108	150	MSV080PN1B	MSV080PN1BSWB	MFV080PN1B
100	32	RB	105x80	80x60	40	128	150	MSV100PN1B	MSV100PN1BSWB	MFV100PN1B
125	32	RB	105x80	80x60	40	155	200	MSV125PN1B	MSV125PN1BSWB	MFV125PN1B
160	40	RB	135x110	105x80	55	195	300	MSV160PN1B	MSV160PN1BSWB	MFV160PN1B
200	50	RB	135x110	105x80	55	235	350	MSV200PN1B	MSV200PN1BSWB	MFV200PN1B



Blue Rubber Tyre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
80	35	RB	105x80	80x60	40	108	150	MSV080RN1B	MSV080RN1BSWB	MFV080RN1B
100	36	RB	105x80	80x60	40	128	160	MSV100RN1B	MSV100RN1BSWB	MFV100RN1B
125	38	RB	105x80	80x60	40	155	200	MSV125RN1B	MSV125RN1BSWB	MFV125RN1B
160	46	RB	135x110	105x80	55	195	300	MSV160RN1B	MSV160RN1BSWB	MFV160RN1B
200	46	RB	135x110	105x80	55	235	350	MSV200RN1B	MSV200RN1BSWB	MFV200RN1B



White Nylon

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
80	32	RB	105x80	80x60	40	108	130	MSV080NY1B	MSV080NY1BSWB	MFV080NY1B
100	36	RB	105x80	80x60	40	128	150	MSV100NY1B	MSV100NY1BSWB	MFV100NY1B
125	40	RB	105x80	80x60	40	155	200	MSV125NY1B	MSV125NY1BSWB	MFV125NY1B
160	50	RB	135x110	105x80	55	195	300	MSV160NY1B	MSV160NY1BSWB	MFV160NY1B
200	50	RB	135x110	105x80	55	235	300	MSV200NY1B	MSV200NY1BSWB	MFV200NY1B



Grey Rubber Tyre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
80	35	RB	105x80	80x60	40	108	70	MSV080GRP1B	MSV080GRP1BSWB	MFV080GRP1B
100	35	RB	105x80	80x60	40	128	75	MSV100GRP1B	MSV100GRP1BSWB	MFV100GRP1B
125	37	RB	105x80	80x60	40	155	100	MSV125GRP1B	MSV125GRP1BSWB	MFV125GRP1B
160	40	RB	135x110	105x80	55	195	135	MSV160GRP1B	MSV160GRP1BSWB	MFV160GRP1B
200	50	RB	135x110	105x80	55	235	205	MSV200GRP1B	MSV200GRP1BSWB	MFV200GRP1B



Black Rubber Tyre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
80	35	RB	105x80	80x60	40	108	70	MSV080BRP1B	MSV080BRP1BSWB	MFV080BRP1B
100	35	RB	105x80	80x60	40	128	75	MSV100BRP1B	MSV100BRP1BSWB	MFV100BRP1B
125	37	RB	105x80	80x60	40	155	100	MSV125BRP1B	MSV125BRP1BSWB	MFV125BRP1B
160	40	RB	135x110	105x80	55	195	135	MSV160BRP1B	MSV160BRP1BSWB	MFV160BRP1B
200	50	RB	135x110	105x80	55	235	205	MSV200BRP1B	MSV200BRP1BSWB	MFV200BRP1B



All available in the following types



Swivel



Swivel Brake



Fixed

MSS Series

Stainless Steel Castor

- Load capacities from 120kg up to 300kg
- Wheel sizes from 80mm to 200mm
- Strong stainless steel bracket
- Double ball race swivel head
- Plain or roller bearing wheels

White Nylon

White Nylon

Plain bearing

Roller bearing

Bolt hole

Wheel Dia. (mm)	Tread Width (mm)	Bolt Hole (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Swivel	Swivel Brake
80	30	12	37	105	150	MSS080NYBH	MSS080NYBBHR	MSS080NYBBH	MSS080NYBBHBR
100	30	12	37	126	150	MSS100NYBH	MSS100NYBBHR	MSS100NYBBH	MSS100NYBBHBR
125	40	12	42	150	150	MSS125NYBH	MSS125NYBBHR	MSS125NYBBH	MSS125NYBBHBR
150	40	12	45	178	200	MSS150NYBH	MSS150NYBBHR	MSS150NYBBH	MSS150NYBBHBR
160	40	16	55	194	300	MSS160NYBH	MSS160NYBBHR	MSS160NYBBH	MSS160NYBBHBR
200	50	16	55	232	300	MSS200NYBH	MSS200NYBBHR	MSS200NYBBH	MSS200NYBBHBR

Top plate

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Total Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
80	30	Plain	100x85	80x60	37	107	150	MSS080NY	MSS080NYBR	MFS080NY
100	30	Plain	100x85	80x60	37	128	150	MSS100NY	MSS100NYBR	MFS100NY
125	40	Plain	115x85	80x60	42	155	150	MSS125NY	MSS125NYBR	MFS125NY
160	40	Plain	140x110	105x80	55	197	300	MSS160NY	MSS160NYBR	MFS160NY
200	50	Plain	140x110	105x80	55	235	300	MSS200NY	MSS200NYBR	MFS200NY



Polyurethane Tyre/Nylon Centre

Polyurethane Tyre/Nylon Centre							Plain bearing		Wheel bearing Key				Roller bearing	
Bolt hole	Wheel Dia. (mm)	Tread Width (mm)w	Bolt Hole (mm)	Offset (mm)	Overall Height (mm)	Load Cap (kg)	Swivel	Swivel Brake	Swivel	Swivel Brake	Swivel	Swivel Brake		
	80	30	12	37	105	120	MSS080PNBH	MSS080PNBBHR	MSS080PNBBH	MSS080PNBBHBR				
	100	30	12	37	126	150	MSS100PNBH	MSS100PNBBHR	MSS100PNBBH	MSS100PNBBHBR				
	125	35	12	42	150	150	MSS125PNBH	MSS125PNBBHR	MSS125PNBBH	MSS125PNBBHBR				
	150	40	12	45	178	150	MSS150PNBH	MSS150PNBBHR	MSS150PNBBH	MSS150PNBBHBR				
	200	50	16	55	232	300	MSS200PNBH	MSS200PNBBHR	MSS200PNBBH	MSS200PNBBHBR				

Top plate	Wheel Dia. (mm)	Tread Width (mm)	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Total Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed	Swivel	Swivel Brake	Fixed
	80	30	100x85	80x60	37	107	120	MSS080PN	MSS080PNBR	MFS080PN	MSS080PNB	MSS080PNBBR	MFS080PNB
	100	30	100x85	80x60	37	128	150	MSS100PN	MSS100PNBR	MFS100PN	MSS100PNB	MSS100PNBBR	MFS100PNB
	125	35	115x85	80x60	42	155	150	MSS125PN	MSS125PNBR	MFS125PN	MSS125PNB	MSS125PNBBR	MFS125PNB
	150	40	115x85	80x60	45	181	150	MSS150PN	MSS150PNBR	MFS150PN	MSS150PNB	MSS150PNBBR	MFS150PNB
	200	50	140x110	105x80	55	235	300	MSS200PN	MSS200PNBR	MFS200PN	MSS200PNB	MSS200PNBBR	MFS200PNB



Elastic Rubber Tyre/Polyamide Centre

Elastic Rubber Tyre/Polyamide Centre

Bolt hole

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Bolt Hole (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake
100	36	RB	12	37	126	150	MSS100RNBH	MSS100RNBHBR
125	36	RB	12	42	150	150	MSS125RNBH	MSS125RNBHBR
160	50	RB	16	55	194	300	MSS160RNBH	MSS160RNBHBR
200	50	RB	16	55	232	300	MSS200RNBH	MSS200RNBHBR

Top plate

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed
80	36	RB	100x85	80x60	37	108	120	MSS080RNB	MSS080RNBHR	MFS080RNB
100	36	RB	100x85	80x60	37	128	150	MSS100RNB	MSS100RNBHR	MFS100RNB
125	36	RB	115x85	80x60	42	155	150	MSS125RNB	MSS125RNBHR	MFS125RNB
160	50	RB	140x110	105x80	55	197	300	MSS160RNB	MSS160RNBHR	MFS160RNB
200	50	RB	140x110	105x80	55	235	300	MSS200RNB	MSS200RNBHR	MFS200RNB



All available in the following types



CASTORS

MG Series

Fabricated Steel Castor

- Load capacities from 200kg up to 600kg
- Wheel sizes from 100mm to 200mm
- Robust fabricated steel bracket
- Double ball race swivel head
- Double pedal brake

Cast Iron

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
100	50	RB	135x110	105x80	35	143	300	KSMG100CIB	KBMG100CIB	KFMG100CIB
125	40	BJ	135x110	105x80	39	165	350	KSMG125CIB	KBMG125CIB	KFMG125CIB
150	45	BJ	135x110	105x80	45	190	500	KSMG150CIB	KBMG150CIB	KFMG150CIB
200	45	BJ	135x110	105x80	56	240	600	KSMG200CIB	KBMG200CIB	KFMG200CIB



Polyurethane Tyre/Cast Iron Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
100	40	BJ	135x110	105x80	35	143	300	KSMG100PCB	KBMG100PCB	KFMG100PCB
125	50	BJ	135x110	105x80	39	165	350	KSMG125PCB	KBMG125PCB	KFMG125PCB
150	50	BJ	135x110	105x80	45	190	500	KSMG150PCB	KBMG150PCB	KFMG150PCB
160	50	BJ	135x110	105x80	45	195	500	KSMG160PCB	KBMG160PCB	KFMG160PCB
200	50	BJ	135x110	105x80	56	240	600	KSMG200PCB	KBMG200PCB	KFMG200PCB



Polyurethane Tyre/Aluminium Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
160	50	BJ	135x110	105x80	45	195	500	KSMG160PAB	KBMG160PAB	KFMG160PAB
200	50	BJ	135x110	105x80	56	240	600	KSMG200PAB	KBMG200PAB	KFMG200PAB



Rubber Tyre/Cast Iron Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
150	50	BJ	135x110	105x80	45	190	400	KSMG150RUB	KBMG150RUB	KFMG150RUB
200	50	BJ	135x110	105x80	56	240	500	KSMG200RUB	KBMG200RUB	KFMG200RUB



White Nylon

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
100	50	BJ	135x110	105x80	35	143	270	KSMG100NYB	KBMG100NYB	KFMG100NYB
125	45	BJ	135x110	105x80	39	165	350	KSMG125NYB	KBMG125NYB	KFMG125NYB
150	50	BJ	135x110	105x80	45	190	500	KSMG150NYB	KBMG150NYB	KFMG150NYB
160	50	BJ	135x110	105x80	45	195	450	KSMG160NYB	KBMG160NYB	KFMG160NYB
200	50	RB	135x110	105x80	56	240	500	KSMG200NYB	KBMG200NYB	KFMG200NYB



Elastic Rubber Tyre/Aluminium Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Braked	Fixed
100	40	BJ	135x110	105x80	35	143	200	KSMG100EAB	KBMG100EAB	KFMG100EAB
125	50	BJ	135x110	105x80	39	165	250	KSMG125EAB	KBMG125EAB	KFMG125EAB
150	50	BJ	135x110	105x80	45	190	300	KSMG150EAB	KBMG150EAB	KFMG150EAB
160	50	BJ	135x110	105x80	45	195	300	KSMG160EAB	KBMG160EAB	KFMG160EAB
200	50	BJ	135x110	105x80	56	240	400	KSMG200EAB	KBMG200EAB	KFMG200EAB



All available in the following types



Swivel



Swivel Brake



Fixed

HK Series

Fabricated Steel Castor

- Load capacities from 250kg up to 1300kg
- Wheel sizes from 125mm to 300mm
- Robust heavy duty fabricated steel bracket
- Double ball race swivel head

Polyurethane Tyre/Cast Iron Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed
125	50	BJ	149x110	105x80	45	177	400	HKS12520241	HKB12520241	HKF12520241
150	50	BJ	149x110	105x80	49	202	730	HKS15020241	HKB15020241	HKF15020241
200	50	BJ	149x110	105x80	54	252	1000	HKS20020241	HKB20020241	HKF20020241
250	50	BJ	149x110	105x80	70	303	1150	HKS25025241	HKB25025241	HKF25025241
300	50	BJ	149x110	105x80	80	353	1300	HKS30025241	HKB30025241	HKF30025241



Cast Iron

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed
125	40	BJ	149x110	105x80	45	177	500	HKS12520441	HKB12520441	HKF12520441
150	45	BJ	149x110	105x80	49	202	600	HKS15020441	HKB15020441	HKF15020441
200	45	BJ	149x110	105x80	54	252	1000	HKS20020441	HKB20020441	HKF20020441
250	54	BJ	149x110	105x80	70	303	1150	HKS25025441	HKB25025441	HKF25025441



White Nylon

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed
125	45	BJ	149x110	105x80	45	177	300	HKS12520111	HKB12520111	HKF12520111
150	50	BJ	149x110	105x80	49	202	600	HKS15020111	HKB15020111	HKF15020111
200	50	BJ	149x110	105x80	54	252	1000	HKS20020111	HKB20020111	HKF20020111
250	50	BJ	149x110	105x80	70	303	1100	HKS25025111	HKB25025111	HKF25025111



Rubber Tyre/Cast Iron Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed
150	50	BJ	149x110	105x80	49	202	370	HKS15020341	HKB15020341	HKF15020341
200	50	BJ	149x110	105x80	54	252	535	HKS20020341	HKB20020341	HKF20020341
250	54	BJ	149x110	105x80	70	303	615	HKS25025341	HKB25025341	HKF25025341
300	54	BJ	149x110	105x80	80	353	680	HKS30025341	HKB30025341	HKF30025341



Elastic Rubber Tyre/Aluminium Centre

Wheel Dia. (mm)	Tread Width (mm)	Bearing	Top Plate (mm)	Bolt Holes (mm)	Offset (mm)	Overall Height (mm)	Load Cap. (kg)	Swivel	Swivel Brake	Fixed
125	50	BJ	149x110	105x80	45	177	250	HKS12520341	HKB12520341	HKF12520341



All available in the following types



Swivel



Swivel Brake



Fixed

KGD Series

Footmaster multifunctional levelling castors

Fixing Type	Wheel Dia. (mm)	Method Of Operating	Top Plate (mm)	Bolt Holes (mm)	Stem Size (mm)	Overall Height (mm)	Load Cap. (kg)		Part Number
							Static	Dynamic	
Stem	42	Handwheel	-	-	M8x15	71+10	50	25	KGD-40S
Top Plate	50	Handwheel	73x73	58x58	-	82+10	250	125	KGD-60F
Stem	50	Handwheel	-	-	M12x18	82+10	250	125	KGD-60S
Top Plate	50	Ratchet	73x73	58x58	-	82+10	250	125	KGDR-60F
Stem	50	Ratchet	-	-	M12x18	82+10	250	125	KGDR-60S
Top Plate	63	Handwheel	90x90	70x70	-	102+15	500	250	KGD-80F
Top Plate	63	Ratchet	90x90	70x70	-	102+15	500	250	KGDR-80F
Top Plate	75	Handwheel	95x95	70x70	-	120+12	750	375	KGD-100F
Stem	75	Handwheel	-	-	M16x24	120+12	750	375	KGD-100S
Top Plate	75	Hex Spanner	95x95	70x70	-	120+12	1000	500	KGD-120F
Top Plate	97	Hex Spanner	100x100	70x70	-	130+15	1500	750	KGD-150F

Designed to offer 360o swivel castor function, this easily operated range offer mobility, levelling and vibration damping features for light to heavy weight equipment. Footmaster multifunctional castors allow users to move and position large equipment single handily. Levelling can be achieved with ease. Static load capacities of 50kg to 1500kg and Dynamic load capacities of 25kg to 750kg offer unrivalled mobility. (KGD-60F,60S,80F & 80S available in black finish or stainless steel)

All available in the following types



KGD S Type
(Optional Black Finish)



KGDR S Type



KGD F Type
(Optional Stainless Steel)